

PRODUCT DESCRIPTION

Cleanrex II is a aliphatic solvent-based washing agent. It contains specially matched surfactants. It removes greases, oils, soot and other industrial contaminants. It does not emit toxic vapours and has a gentle smell. It contains no water. When dried, it provides temporary corrosion protection to steel surfaces.

TYPICAL USES

It is a universal preparation for the cleaning and degreasing of very dirty surfaces.

It is intended for degreasing equipment and machine parts, internal combustion engines and their components, cleaning mechanical gear-boxes and bearings, and washing fuel tanks.

Grease and deposits that are difficult to remove can be cleaned off owing to appropriately chosen solvents.

PRODUCT PROPERTIES

Physical form	clear fluid
Colour	green blue
Functional test	
washing effectiveness	96%
Density	0.80 g/cm ³
Wettability	8 seconds
Foam thickness	35 mm
Surface tension	26 mN/m
Spontaneous ignition temperature	>220°C
Flow temperature	<-45°C
Index of refraction	1.434
Copper plate corrosion test, 3 h at 100°C (ASTM D130)	1

OTHER INFORMATION

Storage

The product should be stored in the original packaging. The storage life of the product amounts to 36 months.

Method of application

Depending on how dirty the element is, the preparation can be diluted with water 1:4. In this state it produces an emulsion of very good washing properties that does not flow down vertical surfaces. The preparation can be used for immersion washing in tanks and applied by brush, paintbrush, sponge or spraying.