

**CLEANREX WK-2**

Product Development Department

January 2006

Page 1 of 1

**PRODUCT DESCRIPTION**

Cleanrex WK-2 is a waterborne washing agent. It contains specially matched surfactants. It removes contamination caused by crude oil derivatives from steel and cast iron, rust and scale deposits. The preparation is characterised by a low surface tension, due to which high washing effectiveness is ensured for the details of complicated shapes, while at the same time a low consumption of the product is maintained. It contains no solvents and phosphates, and is non-flammable. It contains corrosion inhibitors.

**TYPICAL USES**

It is intended for the cleaning and degreasing of equipment and machine parts, washing floors and automobile parts, and derusting.

It can be used in automatic cleaning machines, high-pressure units and ultrasonic washers.

It is not aggressive to the majority of cleaned surfaces (metals, varnishes, plastics, rubber) at working dilutions.

It can be applied cold or hot (up to 60°C).

**Recommended dilutions**

Pressure washing:

1:15 heavily soiled

1:50 lightly soiled

Washing in tanks:

1:15 heavily soiled

1:40 lightly soiled

Washing in ultrasonic washers:

1:30 heavily soiled

1:60 lightly soiled

Derusting:

Undiluted

It is suitable for mechanical cleaning and application by hand.

**PRODUCT PROPERTIES**

Physical form	clear fluid
Colour	pink
pH	1-2
Functional test	
washing effectiveness	98%
Density	1.03 g/cm <sup>3</sup>
Boiling point	>100°C
Index of refraction	1.359

**OTHER INFORMATION****Storage**

The product should be stored in the original packaging at temperatures over 5°C. The storage life of the product amounts to 36 months.

**Method of application**

The preparation should be diluted with water to dilution ratios depending on the level of surface contamination and method of washing. For heavy contamination the product should be diluted to a ratio of 1:15. The preparation can be used for immersion washing in tanks and applied by paintbrush, brush, sponge or spraying. The washing effectiveness of the solution increases at elevated temperatures. Drying of the solution shall be precluded – washed surfaces should be rinsed with water. Absorbed contamination is precipitated from the preparation—in mechanical washers it is retained by filters

**Note**

Before application onto coats of paint, leather, rubber and aluminium alloy surfaces, perform a test on a small surface area.